

Claims:

1. Roof structure (20) for a vehicle (10), comprising:

a rear roof part (24), which comprises a vehicle rear window (26), side, rear pillars (27) and a rear segment (25) of the vehicle roof and which is displaceable on the vehicle chassis in the vehicle longitudinal direction;

a forward roof part (22), which is attachable adjacent to a windshield frame (11) of the vehicle and is removable from the roof structure (20), and its length in the vehicle longitudinal direction corresponds to the displacement path of the rear roof part (24); and

rear, side elements (28), which are attachable adjacent to the rear roof part (24) and are removable from the roof structure (20), and their length in the vehicle longitudinal direction corresponds to the displacement path of the rear roof part.

2. Roof structure (20) according to claim 1, characterized in that the forward roof part (22) and/or the rear, side elements (28) are manually detachable.

3. Roof structure (20) according to one of the preceding claims, characterized in that the vehicle rear window (26) is upwardly pivotable about an axis (11 [sic, A1]) that extends perpendicular to a vehicle longitudinal plane.

4. Roof structure (20) according to one of the preceding claims, characterized in that the forward roof part (22) and the components of the rearward roof part (24) are designed as a rigid structure.

5. Roof structure (20) according to one of the preceding claims, characterized in that forwardly-directed contours of the side, rear pillars (27) and the side contours of the rear segment (25) of the rear roof part (24) correspond to the upper and rear contours of a window (15) of a side vehicle door.

6. Vehicle (10) having the roof structure (20) according to one of the preceding claims.

7. Vehicle (10) according to claim 6, characterized in that a rear part (12) of the vehicle, which borders on the vehicle rear window (26) towards the lower rear, is upwardly pivotable about an

axis (A2) that extends perpendicularly to a vehicle longitudinal plane on the rear-side end of the rear part.

8. Vehicle according to claim 6 or 7, characterized in that the vehicle comprises two front seats, which are disposed in the area of the forward roof part (22), and a rear bench or rear seats, which are disposed in the area of the rear roof part (24), wherein the rear seats/rear bench are/is folded down or removed when the rear roof part is displaced towards the front.

9. Vehicle (10) according to claim 8, characterized in that the rear roof part (24) is pivotable into the vehicle in the forwardly-displaced position.